

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ConnectionID	PushTransportConnectionID	0 to 65534			M
1	TransportOptions	TransportOptionsStruct				M

11.7.9.4.1. ConnectionID Field

This field SHALL be a [PushTransportConnectionID](#) representing the transport to modify.

11.7.9.4.2. TransportOptions Field

This field SHALL represent the [Transport Options](#) to modify.

11.7.9.4.3. Effect on Receipt

The following process SHALL be followed when the server receives this command:

- If the UTCTime attribute of the Time Synchronization cluster is null:
 - Fail the command with the cluster-specific status code of InvalidTime, and end processing with no other side effects.
- If no entry can be found for the passed in *ConnectionID* in the [CurrentConnections](#) list attribute:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the associated fabric of that entry is not the accessing fabric:
 - Fail the command with the status code NOT_FOUND, and end processing with no other side effects.
- If the transport is currently uploading:
 - Fail the command with the status code BUSY, and end processing with no other side effects.
- On that entry, update the [TransportOptions](#) field, of the [TransportConfiguration](#) field, to the passed in *TransportOptions*.

11.7.9.5. SetTransportStatus Command

This command SHALL be generated to request the Node modifies the Transport Status of a specified transport or all transports.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ConnectionID	PushTransportConnectionID	all	X		M