

Condition	Description
TLSClntCond	The node has at least one endpoint where some Device Type present on the endpoint needs to use TLS Client Management. Since TLS requires basic Time Sync support, this will include that dependency.
PowerSourceCond	The node has at least one endpoint where some Device Type present on the endpoint needs to have Power Source be on the Root Node.
ACLExtensionCond	The node has at least one endpoint where some Device Type present on the endpoint needs the Access Control instance to have the Extension attribute.

2.1.4. Device Type Requirements

The table lists other device types to be implemented along with this device type based on conformance.

Device Type ID	Device Type Name	Constraint	Conformance
0x0011	Power Source		PowerSourceCond, O

2.1.5. Cluster Requirements

Each endpoint supporting this device type SHALL include these clusters based on the conformance defined below.

Cluster ID	Cluster Name	Client/Server	Quality	Conformance
0x001F	Access Control	Server	I	M
0x0028	Basic Information	Server	I	M
0x002B	Localization Configuration	Server	I	LanguageLocale
0x002C	Time Format Localization	Server	I	TimeLocale
0x002D	Unit Localization	Server	I	UnitLocale
0x002E	Power Source Configuration	Server	I	O, D
0x0030	General Commissioning	Server	I	M
0x0031	Network Commissioning	Server		!CustomNetworkConfig
0x0032	Diagnostic Logs	Server	I	O