

Cluster ID	Cluster Name	Client/Server	Quality	Conformance
0x002F	Power Source	Server		BridgedPower-SourceInfo
0x0039	Bridged Device Basic Information	Server		M
0x003C	Administrator Commissioning	Server		FabricSynchronizedNode
0x0750	Ecosystem Information	Server		FabricSynchronizedNode, O

2.5.6. Endpoint Composition

A Bridged Node endpoint SHALL support one of the following composition patterns:

- **Separate Endpoints:** All application device types are supported on separate descendant endpoints, and SHALL NOT be hosted on the Bridged Node endpoint. The Bridged Node endpoint's Descriptor cluster PartsList attribute SHALL indicate a list of all endpoints representing the functionality of the bridged device, including the endpoints supporting the application device types, i.e. the full-family pattern defined in the System Model specification.

This is used for the following cases:

- Exposing a compound device - the child endpoints each have a part of the functionality of the bridged device. See endpoints 31-34 in the example below; the bridged device is a PIR sensor which also has temperature and illuminance measurement. Endpoints 32-34 host the associated application device types and clusters. Endpoint 31 (the endpoint with the Bridged Node device type) functions as parent for these endpoints and has no application device types.
- Exposing a composed device type - a child endpoint of the endpoint with the Bridged Node device type has the composed device type; this endpoint with the composed device type has child endpoints for the device type(s) that are mandatory or optional for the composed device type. See endpoints 41-43 in the example below; this is a refrigerator, which is a composed device type, hosted on endpoint 42, with the associated temperature controlled cabinet device type on child endpoint 43. Endpoint 41 (the endpoint with the Bridged Node device type) functions as parent for the endpoint hosting the composed device type and has no application clusters.
- Combinations of the above.
- **One Endpoint:** Both the Bridged Node and one or more application device types are supported on the same endpoint (following application device type rules). The PartsList attribute in the Descriptor cluster SHALL be empty.
Since compound devices and composed device types each need more than one endpoint to expose their functionality, they cannot use the "One Endpoint" pattern and need to use the "Separate Endpoints" model described above.

- Example in the figure below: endpoint 21 hosts the Bridged Node utility device type, plus the application device type for a dimmable light on same endpoint. Since the dimmable light device type is a superset of on/off light, that subset device type MAY be added here as well.