

### 5.1.5. Element Requirements

The table below lists qualities and conformance that override the cluster specification requirements. A blank table cell means there is no change to that item and the value from the cluster specification applies.

| Cluster ID | Cluster Name      | Element   | Name          | Constraint | Access | Conformance |
|------------|-------------------|-----------|---------------|------------|--------|-------------|
| 0x0003     | Identify          | Command   | TriggerEffect |            |        | M           |
| 0x0006     | On/Off            | Feature   | Lighting      |            |        | M           |
| 0x0008     | Level Control     | Feature   | OnOff         |            |        | M           |
| 0x0008     | Level Control     | Feature   | Lighting      |            |        | M           |
| 0x0008     | Level Control     | Attribute | CurrentLevel  | 1 to 254   |        |             |
| 0x0008     | Level Control     | Attribute | MinLevel      | 1          |        |             |
| 0x0008     | Level Control     | Attribute | MaxLevel      | 254        |        |             |
| 0x0062     | Scenes Management | Command   | CopyScene     |            |        | M           |

As the TriggerEffect command of the Identify cluster and the OffWithEffect command of the On/Off cluster specify light effects that require dimming of the light output, and such is not possible on this device type, the specified light effects MAY be replaced by pure on/off light effects.

## 5.2. Dimmable Plug-In Unit Device Type

A Dimmable Plug-In Unit is a device that provides power to another device that is plugged into it, and is capable of being switched on or off and have its level adjusted. The Dimmable Plug-in Unit is typically used to control a conventional non-communicating light through its mains connection using phase cutting.

The [Section 5.4, “Mounted Dimmable Load Control”](#) (added in Matter 1.4) has identical cluster requirements as the Dimmable Plug-In Unit, and is marked as a superset of this device type (since Matter 1.4.2). For devices intended to be mounted permanently, the [Section 5.4, “Mounted Dimmable Load Control”](#) device type SHALL be used, with the Dimmable Plug-In Unit device type optionally added to the DeviceTypeList of the Descriptor cluster in addition to the Mounted Dimmable Load Control device type (see [\[ref\\_MountedDimmableLoadControlServerGuidance\]](#)).

Before Matter 1.4, mounted dimmable load control units typically used the Dimmable Plug-In Unit device type. Clients can encounter devices which were made before or after these specification updates. Therefore, clients SHOULD use the following heuristic to distinguish the type of physical device based on the device type revision found on an endpoint ("--" means the device type is not