

- cluster Switch (feature flags: MS) exposing the events of the bottom-right button
- cluster Descriptor with its TagList containing four tags: **Position.Bottom**, **Position.Right**, **Number.Four** and (Tag=**Switches.Custom**, Label="nightlight")

6.6.5. Relation with other Switch device types (informative)

The Generic Switch device type and the On/Off Light Switch device type both convey information about interactions with a switch to another device.

- The On/Off Light Switch will send On/Off/Toggle commands from its On/Off (client) cluster to a device implementing the On/Off (server) cluster to control the on/off functionality of that device. An On/Off Light Switch device can also implement Groups and Scenes Management clusters and thus send group and scene commands. Basically, it is targeted at directly sending control commands to other devices. The binding table is used to tell the device where to send the commands.
- The Generic Switch device type will send updates of attributes (for Latching Switch only) and events to subscribed parties which implement the Switch client cluster, as indications of interaction with the switch - leaving the interpretation (e.g. which device should be actuated because of the interaction) to the subscribed party. So it can be compared to a sensor-type device. This allows a more comprehensive controller to combine the information from the switch with other inputs or information sources (e.g. time of day, user presence) to determine which control commands (e.g. on/off, scene recall, attribute change) are sent to other devices in the network.

A device manufacturer MAY implement both device types on the same switch device, to allow it to be used for both types of control, as in this example for a rocker switch which implements:

- endpoint 31 with device type On/Off Light Switch which contains
 - (client) cluster On/Off exposing the On/Off/Toggle commands
- endpoint 32 with device type Generic Switch which contains
 - (server) cluster Switch (feature flags: LS) exposing the state and events of the switch

When this device is used in a particular setup, binding tables and subscriptions can be used to determine how it is used:

- used as an On/Off Light Switch (no subscriptions to endpoint 32)
- used as a Generic Switch (no bindings on endpoint 31)
- used as both at the same time. In this case, an interaction with the switch would result in an On/Off/Toggle command being sent to devices listed in the binding table of endpoint 31, as well as attribute update and events being sent towards devices having a subscription with endpoint 32.