

Speaker endpoint on the same node MAY cause HDMI volume up/down commands to be sent to the given HDMI output.

10.1.6.7. Sleep/Wake

This feature controls low power mode on the device which includes functionality such as sleep, and declaration of protocols supported for Wakeup.

The Low Power cluster SHALL be used for putting a device into low power (sleep) mode.

The WakeOnLAN cluster SHALL be used for declaring that a device supports the WakeOnLAN protocol.

10.1.6.8. Target Navigation

This feature controls on-screen navigation to custom-named targets, for example, "Settings", "On Demand" and "Search". A list of named targets can be provided for the Video Player endpoint itself, as well as for Content App represented as endpoints.

The Target Navigator cluster SHALL be used for listing navigation targets, invoking navigation to a target, and tracking the current target.

10.1.6.9. Keypad Navigation

This feature controls on-screen navigation, commonly referred to as D-Pad navigation, and includes navigation commands such as UP, DOWN, LEFT, RIGHT, SELECT, BACK, EXIT, MENU.

The Keypad Input cluster SHALL be used for this functionality.

10.1.6.10. Account Login

This cluster provides commands that facilitate user account login on an application or a node.

The Account Login cluster SHALL be used for this functionality.

10.1.7. Content Launching Features

Many Video Player devices (traditional TVs, Set Top Boxes, Content Streamers) have advanced features that MAY include any of the following:

- the ability to search for and playback content such as movies and TV shows
- a platform for Content Apps that can themselves be launched, and instructed to search and playback content such as movies and TV shows
- the ability to download and playback basic content referenced by URL

10.1.7.1. Discover and Launch Content App from another Device

This feature allows a client to discover the Content App identification catalogs supported by a Video Player device, and launch an Application based upon a Content App identifier within a given catalog. An example Content App identification catalog is the DIAL registry (<http://www.dial->