

Cluster ID	Cluster Name	Client/Server	Quality	Conformance
0x050A	Content Launcher	Server		M
0x050B	Audio Output	Server		O
0x050C	Application Launcher	Server		ContentAppPlatform
0x050E	Account Login	Server		O
0x050F	Content Control	Server		P, O

10.3.5. Element Requirements

The table below lists qualities and conformance that override the cluster specification requirements. A blank entry means no change.

Cluster ID	Cluster Name	Element	Name	Constraint	Access	Conformance
0x050C	Application Launcher	Feature	Application-Platform			M

10.4. Speaker Device Type

This defines conformance to the Speaker device type.

This feature controls the speaker volume of the device.

To control unmute/mute, the On/Off cluster SHALL be used. A value of TRUE for the OnOff attribute SHALL represent the volume on (not muted) state, while a value of FALSE SHALL represent the volume off (muted) state. For volume level control, the Level cluster SHALL be used.

A dedicated endpoint is needed because the On/Off cluster can also be used for other purposes, such as for power control.

The decision to use Level and On/Off clusters for volume (rather than defining a new audio control cluster) was made in order to treat volume in a fashion consistent with lighting which also uses these clusters and has matching functional requirements.

10.4.1. Revision History

Revision	Description
1	Initial revision

10.4.2. Classification