

13.1.5. Cluster Restrictions

13.1.5.1. Temperature Control Cluster (Server) Clarifications

Given that different markets have different customary methods of providing temperature settings (e.g. North America often prefers levels, whereas many other markets provide temperatures in °C), it is RECOMMENDED that when the Temperature Control cluster is present, the TemperatureLevel or TemperatureNumber feature of that cluster is chosen to follow the most widely applied convention for the market where the product is sold.

13.1.5.2. On/Off Cluster (Server) Clarifications

As indicated in the Element Requirements section below, the DF (Dead Front) feature is required for the On/Off cluster in this device type. See the "DeadFrontBehavior feature" section in the On/Off cluster description for detailed requirements. The "dead front" state is linked to the OnOff attribute in the On/Off cluster having the value False. Thus, the Off command of the On/Off cluster SHALL move the device into the "dead front" state, the On command of the On/Off cluster SHALL bring the device out of the "dead front" state, and the device SHALL adhere with the associated requirements on subscription handling and event reporting.

13.1.5.3. Best Effort Attribute Values in "Dead Front" State

When in "dead front", should the operational values of the cluster attributes not be available or accessible, the following are the RECOMMENDED best effort values for per cluster attributes when responding to a new subscription request or a read request. Attributes not listed have no change in their defined or expected values.

Cluster Name	Attribute	Fallback
Laundry Washer Mode	CurrentMode	MS
Laundry Washer Controls	SpinSpeedCurrent	null
	NumberOfRinses	null
	SpinSpeeds	null
	MaxRinses	null
Temperature Control	All attributes	MS
Identify	All attributes	MS
Operational State	PhaseList	null
	CurrentPhase	null
	CountdownTime	null
	OperationalState	Stopped
	OperationalError	No Error

13.1.6. Element Requirements

The table below lists qualities and conformance that override the cluster specification require-