

than the internal light of the microwave oven cavity.

13.11.6. Cluster Requirements

Each endpoint supporting this device type SHALL include these clusters based on the conformance defined below.

Cluster ID	Cluster Name	Client/Server	Conformance
0x0003	Identify	Server	O
0x0060	Operational State	Server	M
0x0202	Fan Control	Server	O
0x005E	Microwave Oven Mode	Server	M
0x005F	Microwave Oven Control	Server	M

When the Fan Control cluster is supported on an endpoint of this device type, it is intended to be used as a ventilation fan when the microwave oven is installed above a range in an "over the range" configuration rather than the internal fan of the microwave oven cavity.

13.11.7. Element Requirements

This lists qualities and conformance that override the cluster specification requirements. A blank table cell means there is no change to that item and the value from the cluster specification applies.

Cluster ID	Cluster Name	Element	Name	Constraint	Access	Conformance
0x0060	Operational State	Attribute	Countdown-Time			M
0x0060	Operational State	Event	OperationCompletion			M
0x0202	Fan Control	Feature	Wind			X
0x0202	Fan Control	Feature	AirflowDirection			X

13.11.8. Cluster Usage

This section describes how to control and monitor the operation of a Microwave Oven device. This information is meant to clarify how the data dependencies within the device type's cluster composition are to be used.

Note that the device operations may also be the result of, or affected by, out-of-band actions such as physical button presses on the device, internally scheduled events, vendor application requests, commands invoked via other fabrics, internal device timeouts, etc. For example, a user may pause the oven during operation by opening the door to check on the food.