

Location	Device Type ID	Device Type Name	Condition	Conformance
Root	0x0016	Root Node	ManagedAclAllowed	O

15.3.5.1. ManagedAclAllowed Condition

A Network Infrastructure Manager device MAY utilize the ManagedAclAllowed condition to allow the Managed Device (MNGD) feature flag of the Access Control Cluster on the device's Root Node endpoint (i.e. Endpoint 0).

Please refer to the "Managed Device Feature Usage Restrictions" section in the Access Control Cluster chapter of the Matter Core Specification for the complete set of limitations on use of this feature on endpoints with the Network Infrastructure Manager device type.

NOTE

The conformance of this element crosses endpoints. It is expressed against the Root Node endpoint and there SHALL NOT be a separate AccessControl cluster on the endpoint having the Network Infrastructure Manager device type.

15.3.6. Other Requirements

The Network Infrastructure Manager SHALL implement a bridged Wi-Fi / Ethernet hub network, enabling IPv6 connectivity between Matter Nodes across transports.

The Network Infrastructure Manager SHALL support IP communication with at least 300 Matter devices on this network. If the Network Infrastructure Manager operates a DHCPv4 server, then it SHOULD be configured by default with a subnet mask and DHCP pool size that allow for at least 300 devices.

NOTE

This recommendation is meant to avoid IPv4 address exhaustion if a large number of devices request IPv4 addresses e.g. for non-Matter traffic.

15.3.6.1. Ethernet Requirements

The device SHALL provide an Ethernet LAN interface that is part of the bridged hub network.

The Root Node endpoint of the device MAY include a Network Commissioning cluster associated with this Ethernet interface.

15.3.6.2. Wi-Fi Requirements

The device SHALL support the operation of an IEEE 802.11 Wi-Fi network (ESS) and provide access to the SSID and credentials of this network via the Wi-Fi Network Management cluster. The mechanisms by which this network is configured are outside the scope of this specification. The device SHALL support concurrently operating BSSs for this ESS in the 2.4 GHz and 5 GHz frequency bands; it MAY support operating additional BSSs for this ESS in other frequency bands such as 6 GHz or sub-1 GHz. All BSSs in this ESS SHALL be part of the bridged hub network, i.e. bridged to each other and to the Ethernet interface.