

num of 64 Thread Children simultaneously in any combination of Children End Device types. The Network Infrastructure Manager device SHALL support operating as a Thread Border Router in any Thread Network with up to 150 Thread nodes.

15.3.6.4. Discovery and Commissioning

A Network Infrastructure Manager device SHOULD implement **Extended Discovery** in order to be discoverable by entities on the local IP network, even when not in Commissioning Mode, and SHOULD populate the optional *device type* subtype (e.g., **_T144**) to allow for filtering of discovery results to find only Nodes that match the Network Infrastructure Manager device type (see **Commissioning Subtypes**).

A Network Infrastructure Manager SHOULD populate the following DNS-SD TXT record key/value pairs in the Commissionable Node Discovery response: **Commissioning Pairing Hint**, and **Commissioning Pairing Instruction** so that the Commissioner can guide the user through the steps needed to put the Commissionee into Commissioning Mode. If the Network Infrastructure Manager provides its own app or website which includes a UX for putting the device into Commissioning Mode, then the device SHOULD populate the **Commissioning VID/PID** key/value pair and SHOULD set bit 1 of the Pairing Hint (Device Manufacturer URL), so that the Commissioner can utilize the URL specified in the **CommissioningCustomFlowUrl** of the **DeviceModel** schema entry indexed by the Vendor ID and Product ID in the **Distributed Compliance Ledger** and utilize flows described in **Custom Commissioning Flow** to redirect the user to a custom app or website specified by the device vendor, and receive the user back following the callback flow which contains the onboarding payload. This flow is described in detail in the Initiating Commissioning section of the Matter Core specification, under the User Journey titled **User-Initiated Beacon Detection, Already Commissioned Device**.

15.4. Thread Border Router Device Type

A Thread Border Router device type provides interfaces for querying and configuring the associated Thread network.

Instances of physical devices categorized as Thread Border Routers encompass standalone Thread Border Routers, conventional application devices like smart speakers, media streamers, and lighting fixtures equipped with a Thread Border Router, as well as Wi-Fi Routers incorporating Thread Border Router functionality.

The necessary hardware and software prerequisites are detailed within the clusters that are mandated by this device type.

15.4.1. Revision History

Revision	Description
1	Initial revision
2	Extend "Other Requirements" section