

15.4.2. Classification

Device Type ID	Device Type Name	Superset Of	Class	Scope
0x0091	Thread Border Router		Simple	Endpoint

15.4.3. Conditions

See the Base Device Type definition for additional conformance tags.

15.4.4. Device Type Requirements

The following table lists other device types to be implemented along with this device type based on conformance.

ID	Name	Constraint	Conformance
0x0019	Secondary Network Interface		O

If a Thread Border Router endpoint supports the Secondary Network Interface device type, then

- The Thread Border Router Management cluster and the Network Commissioning Cluster SHALL reflect the same underlying network configuration, i.e. changes made via either cluster SHALL also be reflected in the other.
- The MaxNetworks attribute in the Network Commissioning Cluster SHALL have a value of 1.

15.4.5. Cluster Requirements

Each endpoint supporting the Thread Border Router device type SHALL include these clusters based on the conformance defined below.

Cluster ID	Cluster Name	Client/Server	Quality	Conformance
0x0035	Thread Network Diagnostics	Server		M
0x0452	Thread Border Router Management	Server		M
0x0453	Thread Network Directory	Server		O

15.4.6. Other Requirements

The device SHALL implement a Thread Border Router as described by the Thread specification, and provide connectivity between the Thread network and a hub network when connected via a functioning adjacent infrastructure link.