

added to the DeviceTypeList of this endpoint.

Snapshot Cameras MAY have an Occupancy Sensor of a different type for occupancy detection independent of the optical sensor. If this sensor is exposed, it SHALL be placed on a child endpoint of the primary camera endpoint, with the corresponding device type Occupancy Sensor, as indicated in the following table:

Device Type ID	Device Type Name	Constraint	Conformance
0x0107	Occupancy Sensor		O

16.6.5. Condition Requirements

The table below lists conditions and conformance values that override the device type definition.

Location	Device Type ID	Device Type Name	Condition	Conformance
Root	0x0016	Root Node	PowerSourceCond	M
Root	0x0016	Root Node	TimeSyncWithTZ-Cond	M

16.6.6. Cluster Requirements

Each endpoint supporting the Snapshot Camera device type SHALL include these clusters based on the conformance defined below.

Cluster ID	Cluster Name	Client/Server	Quality	Conformance
0x0003	Identify	Server		O
0x0406	Occupancy Sensing	Server		O
0x0550	Zone Management	Server		O
0x0551	Camera AV Stream Management	Server		M
0x0552	Camera AV Settings User Level Management	Server		O

16.6.7. Element Requirements

This lists qualities and conformance that override the cluster specification requirements. A blank table cell means there is no change to that item and the value from the cluster specification applies.