

5.4. Device Discovery	300
5.4.1. Purpose and Scope	300
5.4.2. Announcement by Device	301
5.4.3. Discovery by Commissioner	314
5.5. Commissioning Flows	316
5.5.1. Commissioning Flows Error Handling	322
5.5.2. Commissioning Flow Diagram	323
5.6. Administrator Assisted Commissioning Flows	324
5.6.1. Introduction	324
5.6.2. Basic Commissioning Method (BCM)	324
5.6.3. Enhanced Commissioning Method (ECM)	325
5.6.4. Open Commissioning Window	326
5.7. Device Commissioning Flows	327
5.7.1. Standard Commissioning Flow	327
5.7.2. User-Intent Commissioning Flow	328
5.7.3. Custom Commissioning Flow	330
5.7.4. Enhanced Setup Flow (ESF)	337
5.7.5. Commissioning Fallback Mechanism	346
5.7.6. Onboarding Payload Inclusion (Manual Pairing Code, QR Code, NFC Tag)	348
5.8. In-field Upgrade to Matter	350
5.9. Network Recovery	350
5.9.1. Network Recovery channels	351
5.9.2. Implementer Considerations	351
5.9.3. Network Recovery Flow	351
6. Device Attestation and Operational Credentials	355
6.1. Certificate Common Conventions	355
6.1.1. Encoding of Matter-specific RDNs	355
6.1.2. Key Identifier Extension Constraints	357
6.1.3. Certificate Sizes	357
6.1.4. Presentation of example certificates	357
6.2. Device Attestation	358
6.2.1. Introduction	358
6.2.2. Device Attestation Certificate (DAC)	358
6.2.3. Device Attestation Procedure	373
6.2.4. Device attestation revocation	376
6.3. Certification Declaration	381
6.3.1. Certification Declaration (CD) Format	381
6.3.2. Firmware Information	385
6.3.3. Firmware information validation examples	386
6.4. Node Operational Credentials Specification	388
6.4.1. Introduction	388