

Term	Definition
Ecosystem	A collaborative set of functional entities (proximal- or cloud-based) that provide user-facing configuration and information tools and services, which is provided by one or more cooperating companies. An “ecosystem” to the user is the vendor of the “functional entities” which include, but are not limited to, a smartphone OS, tablet, smartphone app, tablet app, computer app, voice assistant, TV interface, wall display/switch, cloud service, or an integrated service across hardware and software platforms.
Endpoint	A particular component within a Node that is individually addressable.
Endpoint Address	The address assigned to an Endpoint.
Fabric	A logical collection of communicating Nodes, sharing a common root of trust, and a common distributed configuration state.
Information Element	A Wi-Fi (IEEE 802.11-2020) data container used to convey various information regarding a particular Wi-Fi network’s capabilities and operation.
Joint Fabric	A single fabric with a single root of trust that is administered by one or more Ecosystems which each provide a Node implementing the Joint Fabric Administrator device type.
Key Center	A system component which takes the NOCSR from a Commissioner and allocates an Operational Node ID that is unique to the Fabric, inserts this Operational Node ID as the DN into the NOC, and signs the NOC.
Manual Pairing Code	An 11-digit or 21-digit numeric code that can be manually entered/spoken instead of scanning a QR code, which contains the information needed to commission a Matter device.
Network	A set of nodes that have addressability, connectivity, and reachability to one another via Internet Protocol.
NFC-based Commissioning	Commissioning using NFC as a transport layer (NTL) before joining the operational network.
NFC Onboarding Payload	Onboarding payload stored in an NFC Tag .
Node	An addressable entity which supports the Matter protocol stack and (once Commissioned) has its own Operational Node ID and Node Operational credentials.
Operational Discovery	Discovery of a previously commissioned Node for the purpose of performing operations with that Node.
Onboarding Payload	The information needed to start the process of commissioning a Device.
OTA Provider	A Node implementing the OTA Software Update Provider role (see OTA Software Update Provider Cluster).
OTA Requestor	A Node implementing the OTA Software Update Requestor role (see OTA Software Update Requestor Cluster).