

| Term                             | Definition                                                                                                                                                                                                             |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Attestation Authority    | An entity which operates a root level Certificate Authority for the purpose of Device Attestation.                                                                                                                     |
| Product Attestation Intermediate | An entity which operates an intermediate level Certificate Authority for the purpose of Device Attestation.                                                                                                            |
| Product ID (PID)                 | A 16-bit number that identifies the type of a Device, uniquely among the product types made by a given vendor. See <a href="#">Product ID</a> .                                                                        |
| QR Code                          | A machine-readable optical label that contains information about the item to which it is attached (see <a href="#">QR Code</a> ).                                                                                      |
| Rendezvous                       | The process for commissioner and commissionee to establish an initial communication channel.                                                                                                                           |
| Role                             | Some set of (related) behaviors of a Node. Each Node can have multiple roles.                                                                                                                                          |
| Router                           | A device that provides routing services in its network in cooperation with other Routers.                                                                                                                              |
| Secure Channel                   | A channel in which messages are encrypted and authenticated. Unicast secure channels also provide authentication of each peer.                                                                                         |
| Server                           | A Cluster interface that typically supports all or most of the attributes of the Cluster. A Server Cluster communicates with a corresponding remote Client Cluster with the same Cluster identifier.                   |
| Service Discovery                | The ability of a Node to locate services of interest.                                                                                                                                                                  |
| Setup Code                       | The low-entropy passcode used to secure commissioning.                                                                                                                                                                 |
| Software Image                   | A data blob, equivalent to a file, utilized by a Node to update its software. For the purposes of OTA Software Update, this further refers to files conforming to the <a href="#">OTA Software Image File Format</a> . |
| Thread                           | A low-power IEEE 802.15.4-based IPv6 mesh networking technology (see <a href="#">Thread specification</a> ).                                                                                                           |
| Vendor                           | A party who makes or provides one of the functional entities that implement the Matter standard.                                                                                                                       |
| Vendor ID (VID)                  | A 16-bit number that uniquely identifies the Vendor of the Device. See <a href="#">Vendor ID</a> .                                                                                                                     |

## 1.4. Standards Terminology Mapping

| Matter        | HomeKit            | Weave              | Thread       | Zigbee      |
|---------------|--------------------|--------------------|--------------|-------------|
| Administrator | Admin              | Fabric provisioner | Commissioner | Coordinator |
| Attribute     | Characteristics    | Property           |              | Attribute   |
| Binding       | Event subscription | Subscription       | Link         | Binding     |
| Broadcast     |                    |                    | Broadcast    | Broadcast   |
| Client        |                    | Service client     | Client       | Client      |