

2.11.2.2. Subscribe Interaction Limits

- A publisher SHALL ensure that every fabric the node is commissioned into can support at least three [Subscribe Interactions](#) to the publisher and that each subscription SHALL support at least 3 attribute/event paths.
- A server MAY permit [Subscribe Interactions](#) even when there is no accessing fabric, subject to available resources (e.g over PASE).
- Device type specifications MAY require a larger number of supported subscriptions or paths.
- [SUBSCRIPTION_MAX_INTERVAL_PUBLISHER_LIMIT](#) defines the upper limit for the publisher-selected maximum interval for any subscription.
 - If the publisher is an [ICD](#), this SHALL be set to the [Idle Mode Duration](#) or 60 minutes, whichever is greater.
 - Otherwise, this SHALL be set to 60 minutes.
- The minimal supported capabilities, subject to the minimal constraints above, are reported in the CapabilityMinima attribute of the [Basic Information cluster](#).

2.11.2.3. Invoke Interaction Limits

- An [Invoke Request action](#) MAY contain multiple [concrete command paths](#), if supported by the server, but the total number of commands included in a single Invoke Request action is still limited by the maximum message size constraints.

2.12. List of Provisional Items

The following is a list of provisional items.

2.12.1. Invoke Wildcard Paths

Support for an Invoke Interaction with [wildcard paths](#) is provisional.

2.12.2. WildcardPathFlags options

Support for [WildcardPathFlags](#) option in wildcard expansion is provisional.

2.12.3. Tag compression encoding for AttributePathIB, EventPathIB, and AttributeDataIB

The [Section 10.6.2.1, “EnableTagCompression”](#) mechanism for encoding the interaction model is provisional.

2.12.4. CacheAndSync Feature on the GroupKeyManagement cluster

Support for the CacheAndSync feature on the GroupKeyManagement cluster is provisional (see [Section 11.2.4, “Features”](#)).