

Function and description
<pre>byte[CRYPTO_HASH_LEN_IN_BYTES] Crypto_Hash(byte[] message)</pre>
Returns the cryptographic hash digest of the message .
Mapping (Version 1.0)
<pre>int CRYPTO_HASH_LEN_BITS := 256</pre>
<pre>int CRYPTO_HASH_LEN_BYTES := 32</pre>
<pre>Crypto_Hash(message) := byte[CRYPTO_HASH_LEN_BYTES] SHA-256(M := message)</pre>
SHA-256() SHALL be computed as defined in Section 6.2 of FIPS 180-4 .

3.4. Keyed-Hash Message Authentication Code (HMAC)

Crypto_HMAC() computes the cryptographic keyed-hash message authentication code of a message.

Function and description
<pre>byte[CRYPTO_HASH_LEN_BYTES] Crypto_HMAC(byte[] key, byte[] message)</pre>
Returns the cryptographic keyed-hash message authentication code of a message using the given key .
Mapping (Version 1.0)
<pre>Crypto_HMAC(key, message) := byte[CRYPTO_HASH_LEN_BYTES] HMAC(K := key, text := message)</pre>
HMAC() SHALL be computed as defined in FIPS 198-1 using Crypto_Hash() as the underlying hash function H (this is also referred to as HMAC-SHA256()) and CRYPTO_HASH_LEN_BYTES is defined in Section 3.3, “Hash function (Hash)” .

3.5. Public Key Cryptography

Matter specifies the following scheme and parameters for public key cryptography.

3.5.1. Group

The public key cryptography of Matter relies on the group defined in the following mapping table.