

Mapping (Version 1.0)

```

Crypto_Privacy_Encrypt(K, M, N) :=
    byte[lengthInBytes(M)]
    AES-CTR-Encrypt(K := K, P := M, N := N)

```

AES-CTR-Encrypt() SHALL be the encryption function described in Section 6.5 of [NIST 800-38A](#) with the sequence of counters **T** being generated according to the counter generation function of Appendix A.3 of [NIST 800-38C](#) using **N** and the value of **q = 2**; returns the encrypted message as a byte array.

3.7.2. Privacy decryption**Function and description**

```

byte[lengthInBytes(C)]
Crypto_Privacy_Decrypt(
    SymmetricKey K,
    byte[lengthInBytes(C)] C,
    byte[CRYPTO_PRIVACY_NONCE_LENGTH_BYTES] N)

```

Performs the decryption of **C** using the key **K** and a nonce **N**; the output **M** is the decryption of **C**

Mapping (Version 1.0)

```

Crypto_Privacy_Decrypt(K, C, N) :=
    byte[lengthInBytes(C)]
    AES-CTR-Decrypt(K := K, C := C, N := N)

```

AES-CTR-Decrypt() SHALL be the decryption function described in Section 6.5 of [NIST 800-38A](#) with the sequence of counters **T** being generated according to the counter generation function of Appendix A.3 of [NIST 800-38C](#) using **N** and the value of **q = 2**; returns the decrypted message as a byte array.

3.8. Key Derivation Function (KDF)

Matter specifies the following key derivation function to generate encryption keys.