

Mapping (Version 1.0)

Crypto_PAKEValues_Initiator := (**w0**, **w1**) where **w0** and **w1** SHALL be computed as follows:

```
CRYPTO_W_SIZE_BYTES := CRYPTO_GROUP_SIZE_BYTES + 8
CRYPTO_W_SIZE_BITS := CRYPTO_W_SIZE_BYTES * 8

byte w0s[CRYPTO_W_SIZE_BYTES] || byte w1s[CRYPTO_W_SIZE_BYTES] =
    (byte[2 * CRYPTO_W_SIZE_BYTES])
    bit[2 * CRYPTO_W_SIZE_BITS]
    Crypto_PBKDF(passcode, salt, iterations, 2 * CRYPTO_W_SIZE_BITS)
byte w0[CRYPTO_GROUP_SIZE_BYTES] = w0s mod p
byte w1[CRYPTO_GROUP_SIZE_BYTES] = w1s mod p
```

where:

- **mod** is the mathematical modulo operation and **||** is the string concatenation or split operator.
- **passcode**, is the Passcode defined in [Section 5.1.1.6, “Passcode”](#), serialized as little-endian over 4 octets. For example, passcode **18924017** would be encoded as the octet string **f1:c1:20:01** and the passcode **00000005** would be encoded as the octet string **05:00:00:00**.
- **p** is the order of the underlying elliptic curve.
- Both **w0s** and **w1s** SHALL have a length equal to **(CRYPTO_GROUP_SIZE_BYTES + 8)**.
- **salt** and **iterations** are extracted from the **Crypto_PBKDFParameterSet** values.
- The pair (**w0,w1**) is also referred to as Commissioner PAKE input