

that match the upper 4 bits of the discriminator code, as provided in the [manual pairing code](#).

The optional *Vendor ID* subtype (e.g., **_V123**) enables a vendor-specific app to achieve filtering of results to find only Nodes that match that Vendor ID.

The *Commissioning Mode* subtype (e.g., **_CM**) enables filtering of results to find only Nodes that are currently in Commissioning Mode. Note that the subtype is **_CM** regardless of whether the TXT record for commissioning mode is set to 1 (**CM=1**), 2 (**CM=2**) or 3 (**CM=3**). A Commissionee that is not in commissioning mode (**CM=0**) SHALL NOT publish this subtype.

The optional *device type* subtype (e.g., **_T10**) enables filtering of results to find only Nodes that match the device type, generally used for the [User-Initiated Beacon Detection, Not Yet Commissioned Device](#) and the [User-Initiated Beacon Detection, Already Commissioned Device](#) use cases.

In the event that a vendor-specific app wishes to show the user only some of that vendor's Commissionees awaiting commissioning but not all of them, any desired filtering logic (based upon arbitrary criteria, not only Product ID) MAY be implemented within that vendor's proprietary commissioning app.

4.3.1.4. TXT Records

After discovery, IPv6 addresses are returned in the AAAA records and key/value pairs are returned in the DNS-SD TXT record.

Nodes SHALL publish AAAA records for all available IPv6 addresses upon which they are willing to accept Matter commissioning messages.

TXT records available for Commissionable Node Discovery include the common TXT record key/value pairs defined in [Section 4.3.4, "Common TXT Key/Value Pairs"](#).

Commissioners SHALL silently ignore TXT record keys that they do not recognize. This is to facilitate future evolution of this specification without breaking backwards compatibility with existing Commissioners that do not implement the new functionality.

The following subsections describe key/value pairs that are defined specifically for Commissionable Node discovery.

4.3.1.5. TXT key for discriminator (D)

The key **D** SHALL provide the full 12-bit [discriminator](#) for the Commissionable Node and SHALL be present in the DNS-SD TXT record.

The discriminator value SHALL be encoded as a variable-length decimal number in ASCII text, with up to four digits, omitting any leading zeroes.

Any key **D** with a value mismatching the aforementioned format SHALL be silently ignored.

As an example, value **D=840** would indicate that this Commissionable Node has decimal long discriminator **840**. When needed, the upper 4 bits of the discriminator provided by the [manual pairing code](#) can be algorithmically derived from the full discriminator.