

steps only performed when both the Commissionee and Commissioner are instructed to use the [Joint Commissioning Method](#).

A key value of 2 or 3 MAY be used to disambiguate collisions of discriminators between uncommissioned Nodes and commissioned Nodes announcing after a commissioning window was opened. A key value of 2 or 3 serves as a hint to Commissioners to possibly expect multiple Nodes with the same discriminator (see [Section 4.3.1.5, “TXT key for discriminator \(D\)”](#)), and to instruct the user to enter the Onboarding Payload [presented](#) by another Administrator rather than a code provided by the Commissionee.

Since [Extended Discovery](#) can be disabled by the customer, a key value of 0 may not ever be returned by a publisher. When Extended Discovery is disabled and the publisher is not in commissioning mode, then the publisher will not respond to Commissionable Node Discovery.

4.3.1.8. TXT key for device type (DT)

The optional key **DT** MAY be used to provide the publisher’s [Primary Device Type](#). If present, it SHALL be encoded as a variable-length decimal number in ASCII text, omitting any leading zeroes.

For example, the **DT=10** key/value pair would indicate that the primary device type is 10 (0x000A), which is the device type identifier for a Door Lock.

4.3.1.9. TXT key for device name (DN)

The optional key **DN** MAY provide a device advertisement name. If present, it SHALL be encoded as a valid UTF-8 string with a maximum length of 32 bytes (matching the maximum length of the Node-Label string in the [Basic Information Cluster](#)).

When provided, the source of this value SHALL be editable by the user with use clearly designated as being for on-network advertising and MAY be the value stored in the NodeLabel attribute of the [Basic Information Cluster](#) of the Node.

To protect customer privacy on public networks, if a Commissionee supports this key/value pair, then the Commissionee SHALL provide a way for the customer to disable its inclusion.

A Commissionee SHOULD NOT include this field unless doing so for specific use cases which call for it.

For example, the **DN=Living Room** key/value pair indicates that the advertisement name specified by the user is 'Living Room'.

4.3.1.10. TXT key for rotating device identifier (RI)

The optional key **RI** MAY provide a [Rotating Device Identifier](#).

If present, the value associated with the **RI** key SHALL contain the octets of the Rotating Device Identifier octet string encoded as the concatenation of each octet’s value as a 2-digit uppercase hexadecimal number.

The resulting ASCII string SHALL NOT be longer than 100 characters, which implies a Rotating Device Identifier of at most 50 octets.