

- **TargetOperationalFabricID** is the octet string for the Fabric ID as it appears in the advertised Node's **Operational Certificate's** **subject** field, under the **1.3.6.1.4.1.37244.1.5** RDN, that is, a 64-bit unsigned integer scalar in big-endian byte order.

For example, if the root public key for a given Operational Certificate chain containing the identity to be advertised were the following:

pub:

```
04:4a:9f:42:b1:ca:48:40:d3:72:92:bb:c7:f6:a7:e1:
1e:22:20:0c:97:6f:c9:00:db:c9:8a:7a:38:3a:64:1c:
b8:25:4a:2e:56:d4:e2:95:a8:47:94:3b:4e:38:97:c4:
a7:73:e9:30:27:7b:4d:9f:be:de:8a:05:26:86:bf:ac:
fa
```

Then the value for **TargetOperationalRootPublicKey** to use in the derivation of the compressed Fabric Identifier would be without the leading **04**:

```
4a:9f:42:b1:ca:48:40:d3:72:92:bb:c7:f6:a7:e1:1e:
22:20:0c:97:6f:c9:00:db:c9:8a:7a:38:3a:64:1c:b8:
25:4a:2e:56:d4:e2:95:a8:47:94:3b:4e:38:97:c4:a7:
73:e9:30:27:7b:4d:9f:be:de:8a:05:26:86:bf:ac:fa
```

If using the above **TargetOperationalRootPublicKey** and a **TargetOperationalFabricID** value of **0x2906_C908_D115_D362** (octet string **29:06:c9:08:d1:15:d3:62** in big-endian), then the **Compressed-FabricIdentifier** to use in advertising would be **87E1B004E235A130** (octet string **87:e1:b0:04:e2:35:a1:30**).

4.3.2.3. Operational Service Type

The DNS-SD service type [RFC 6335] for Matter Operational Discovery is **_matter._tcp**. Note that the string **_tcp** is boilerplate text inherited from the original DNS SRV specification [RFC 2782], and doesn't necessarily mean that the advertised application-layer protocol runs only over TCP. It is merely mnemonic text which is there to help human readers, and in no way affects software advertising or using the application-layer protocol identified by that unique IANA-recorded service type string.

The following subtype is defined:

1. Compressed Fabric Identifier **_I<hhhh>**, where **<hhhh>** is the **Compressed Fabric Identifier** encoded as exactly 16 uppercase hexadecimal characters, for example **_I87E1B004E235A130** for the Compressed Fabric Identifier example of the previous section. This subtype enables filtering of devices per Fabric if service enumeration (browsing) is attempted, to reduce the set of results to Nodes of interest with operational membership in a given Fabric..