

```
avahi-publish-address B75AFB458ECD.local fe80::f515:576f:9783:3f30
```

A Matter controller can discover the current IPv6 address and port for a known commissioned Matter Node:

```
dns-sd -L 87E1B004E235A130-8FC7772401CD0696 _matter._tcp  
87E1B004E235A130-8FC7772401CD0696._matter._tcp.local. can be reached at  
B75AFB458ECD.local.:22222
```

```
dns-sd -Gv6 B75AFB458ECD.local  
fe80::f515:576f:9783:3f30
```

or

```
avahi-browse _matter._tcp -r  
  
hostname = [B75AFB458ECD.local]  
address = [fe80::f515:576f:9783:3f30]  
port = [22222]
```

4.3.3. Commissioner Discovery

A Commissionee MAY initiate the commissioning process by discovering Commissioners on the network (see [Section 5.2.2.4, “Commissioner Discovery, from an On-Network Device”](#)). This MAY be done using *Commissioner Discovery* described in this section.

With Commissioner Discovery, a Commissionee, upon user interaction, MAY discover Commissioners on the network and obtain a list of information for each which may include Vendor ID, Product ID and friendly name. A Commissionee with a user interface, such as a Television, Thermostat or Video Player device, MAY display the list of discovered commissioners to the user for selection. Once selected, the Commissionee MAY use the [User Directed Commissioning](#) protocol with the Commissioner to indicate that the user has selected it for commissioning of the Commissionee. The Commissioner Discovery service records thus enable a form of "door bell" protocol to allow a Commissionee to request Commissioning.

The Commissioner Discovery feature is optional for both the Commissionee and the Commissioner. Any mandatory requirements described in this section SHALL apply only if the Node or the Commissioner supports this feature. To protect customer privacy on public networks, a Matter Commissioner SHALL provide a way for the customer to set a timeout on Commissioner Discovery, or otherwise disable Commissioner Discovery.

For Commissioner Discovery, the DNS-SD instance name is generated the same way it is done for Commissionable Node Discovery and has the same requirements (uniqueness on local network, and collision detection and recovery) as those in Commissionable Node Discovery, but the requirements for when a new instance name is selected from Commissionable Node Discovery do not