

Unsecured Session SHALL have no encryption, privacy, or message integrity checking.

A *Secure Unicast Session* SHALL be indicated when Session Type is Unicast Session and Session ID is NOT 0.

4.4.1.4. Message Counter (32 bits)

An unsigned integer value uniquely identifying the message from the perspective of the sending node. The message counter is [generated](#) based on the Session Type and increases monotonically for each unique message generated. When messages are retransmitted, using the reliable messaging capabilities, the counter remains the same, as logical retransmission is of a given message as identified by its message counter. Similarly, [acknowledgements](#) refer to values of the message counter being acknowledged.

NOTE

The Message Counter field is scoped to a given Encryption Key. Also, the Message Counter values are independent for control messages and data messages, as indicated by the [C Flag](#). So it is possible to have the same Message Counter for two messages encrypted with different keys, as well as two messages encrypted with the same key but different values of the [C Flag](#).

4.4.1.5. Source Node ID (64 bits)

An optional sequence of 8 bytes containing the unique identifier of the source node. The Source Node ID field SHALL only be present in a message when the [S Flag](#) in the Message Flags field is set to 1.

4.4.1.6. Destination Node ID

The optional Destination Node ID field contains the unique Node Identifier of the destination Node or group to which the message is being sent. The size and encoding of the Destination Node ID field depends on the value of the [DSIZ](#) field.

4.4.1.7. Message Extensions (variable)

The Message Extensions field is a variable length block of data for providing backwards compatible extensibility. The format of the Message Extensions block is shown in [Table 12, “Message Extensions block format definition”](#). The Message Extensions block SHALL be present only if the [MX Flag](#) is set to 1 in the Security Flags field.

Table 12. Message Extensions block format definition

Length	Field
2 bytes	Message Extensions Payload Length, in bytes
variable	[Message Extensions Payload]

If the [MX Flag](#) is set to 1, the Message Extensions Payload Length field SHALL be present and SHALL contain the length of the Message Extensions Payload. The Message Extensions Payload Length field SHALL NOT be privacy obfuscated.