

V Flag (1 bit, position 4)

The Vendor (V) protocol flag is a single bit field which, when set, SHALL indicate whether the Protocol Vendor ID is present.

4.4.3.2. Protocol Opcode (8 bits)

An unsigned integer value identifying the type of the message. The Protocol Opcode is interpreted relative to the Matter protocol specified in the [Protocol ID](#) field.

Opcodes are defined by the corresponding Protocol specification, for example [Secure Channel Protocol](#).

4.4.3.3. Exchange ID (16 bits)

An unsigned integer value identifying the exchange to which the message belongs. An Exchange ID is allocated by the initiator of the exchange, and is unique within the initiator exchange number space as specified in [Section 4.10.2, “Exchange ID”](#).

4.4.3.4. Protocol ID (16 bits)

An unsigned integer value identifying the protocol in which the [Protocol Opcode](#) of the message is defined.

When the [Protocol Vendor ID](#) is the [Matter Standard Vendor ID](#), the Protocol ID SHALL have one of the values specified by [Table 14, “Protocol IDs for the Matter Standard Vendor ID”](#).

Table 14. Protocol IDs for the [Matter Standard Vendor ID](#)

Range	Type	Message Specification
0x0000	PROTOCOL_ID_SECURE_CHANNEL	Section 4.11.1, “Secure Channel Protocol Messages”
0x0001	PROTOCOL_ID_INTERACTION_MODEL	Section 10.2.1, “IM Protocol Messages”
0x0002	PROTOCOL_ID_BDX	Section 11.22.3.1, “BDX Protocol Messages”
0x0003	PROTOCOL_ID_USER_DIRECTED_COMMISSIONING	Section 5.3.2, “UDC Protocol Messages”
0x0004	PROTOCOL_ID_FOR_TESTING	Reserved for bespoke protocols run in an isolated test environment.
0x0005 - 0xFFFF	reserved	reserved

4.4.3.5. Protocol Vendor ID (16 bits)

An optional, unsigned integer value that contains the Vendor ID namespacing for the [Protocol ID](#) field. This field SHALL only be present when the [V Flag](#) is set; otherwise the default is 0, corresponding to the [Matter Standard Vendor ID](#).