

ing of Outgoing Messages”.

3. Set the Security fields as follows:
 - a. The **Session ID** field SHALL be set to the value provided to step 1.
 - b. The **Security Flags** field SHALL be set to the value provided to step 1 with the following sub-fields updated:
 - i. The **Session Type** field SHALL be set to the value obtained from step 1.
4. Set the **Message Flags**, **Destination Node ID**, and **Source Node ID** fields as follows:
 - a. If the Session Type is a unicast session:
 - i. Set **S Flag** to 0.
 - ii. Set **DSIZ** to 0.
 - iii. Omit both **Destination Node ID**, and **Source Node ID**.
 - b. Else if the **Session Type** is a group session:
 - i. Set **S Flag** to 1.
 - ii. Set **DSIZ** to 2.
 - iii. Set **Source Node ID** field to the **operational node id** of the sending node.
 - iv. Set **Destination Node ID** field to the 16-bit Group ID derived from the Destination Node ID.
5. Set the **Message Counter** field to the outgoing message counter from step 2.
6. Execute the AEAD generate and encrypt operation, as specified in [Section 3.6.1, “Generate and encrypt”](#), with the following instantiations:
 - a. The bit string key K SHALL be the Encryption Key obtained from step 1;
 - b. The nonce N SHALL be the **CRYPTO_AEAD_NONCE_LENGTH_BYTES**-octet string constructed according to [Table 17, “Nonce”](#);
 - c. The parameter P SHALL be the Message Payload;
 - d. The additional data octet string A SHALL be the Message Header contents, using little-endian byte order for all scalars, exactly as they appear in the message segments from which they originate:

Message Flags || Session ID || Security Flags || Message Counter

with the optional fields appended according to the Message Flags:

[Source Node ID] || [Destination Node ID] || [Message Extensions]

- e. $C = \text{Crypto_AEAD_GenerateEncrypt}(K, P, A, N)$
7. If the AEAD operation invoked in step 6 results in an error, then security processing SHALL fail and no further security processing SHALL be done on this message.
8. Let C be the output from step 6. C contains the tag of **CRYPTO_AEAD_MIC_LENGTH_BITS** bits (Message