

Parameter Name	Description	Default Value
<i>MAX_TCP_MESSAGE_SIZE</i>	Maximum size of the message carried over TCP, excluding the framing message length field, that the node is capable of receiving from its peer.	64000 bytes.

These parameters are encoded in the following TLV format when included in CASE / PASE session establishment:

```
session-parameter-struct => STRUCTURE [ tag-order ]
{
  SESSION_IDLE_INTERVAL      [1, optional] : UNSIGNED INTEGER [ range 32-bits ],
  SESSION_ACTIVE_INTERVAL    [2, optional] : UNSIGNED INTEGER [ range 32-bits ],
  SESSION_ACTIVE_THRESHOLD    [3, optional] : UNSIGNED INTEGER [ range 16-bits ],
  DATA_MODEL_REVISION        [4]           : UNSIGNED INTEGER [ range 16-bits ],
  INTERACTION_MODEL_REVISION [5]           : UNSIGNED INTEGER [ range 16-bits ],
  SPECIFICATION_VERSION       [6]           : UNSIGNED INTEGER [ range 32-bits ],
  MAX_PATHS_PER_INVOKE        [7]           : UNSIGNED INTEGER [ range 16-bits ],
  SUPPORTED_TRANSPORTS        [8]           : UNSIGNED INTEGER [ range 16-bits ],
  MAX_TCP_MESSAGE_SIZE        [9, optional] : UNSIGNED INTEGER [ range 32-bits ],
}
```

For backwards compatibility, if any tag after tag 2 (*SESSION_ACTIVE_INTERVAL*) is present, then the *SESSION_ACTIVE_INTERVAL* SHALL also be present.

NOTE

That means that *SESSION_ACTIVE_INTERVAL* is always present if the sender of the CASE/PASE session establishment message supports *DATA_MODEL_REVISION*, *INTERACTION_MODEL_REVISION*, and *SPECIFICATION_VERSION*, but recipients SHALL NOT assume that it is present.

For backwards compatibility, if the *DATA_MODEL_REVISION* field is missing, it implies a DataModelRevision value of either 16 or 17.

For backwards compatibility, if the *INTERACTION_MODEL_REVISION* field is missing, it implies a value of either 10 or 11.

For backwards compatibility, if the *SPECIFICATION_VERSION* field is missing, it implies a SpecificationVersion value strictly smaller than 0x01030000.

For backwards compatibility, if the *MAX_PATHS_PER_INVOKE* field is missing, it implies a MaxPathsPerInvoke set to 1.

For backwards compatibility, if the *SUPPORTED_TRANSPORTS* field is missing, it implies that the node only supports [MRP](#). When present with a value of 0, it indicates that the node only supports [MRP](#).