

could choose any non-zero session identifier besides 0x0001 and 0x0002.

If there are no available session identifiers (i.e. the participant has 65,535 open sessions), the Node SHALL terminate an existing session to free a session identifier.

4.13.3. Application Data Phase

When the last **CASE** or **PASE** protocol message is sent or received and successfully processed, session establishment has completed.

4.13.3.1. Secure Session Context

During the Application Data Phase, the following conceptual session context data SHALL be utilized to securely process subsequent messages:

1. **Session Type**: Records whether the session was established using **CASE** or **PASE**.
2. **Session Role**: Records whether the node is the session initiator or responder.
3. **Local Session Identifier**: Individually selected by each participant in secure unicast communication during session establishment and used as a unique identifier to recover encryption keys, authenticate incoming messages and associate them to existing sessions.
 - On a given Node, this is the identifier that SHALL be used to map from an incoming message's Session ID field to the session context data.
4. **Peer Session Identifier**: Assigned by the peer during session establishment.
 - On a given Node, this is the identifier that SHALL be used in the **Session ID** field of every outgoing message associated with the session, so that it can be interpreted as the **Local Session Identifier** by the remote peer.
5. **I2RKey**: Encrypts data in messages sent from the initiator of session establishment to the responder.
6. **R2IKey**: Encrypts data in messages sent from the session establishment responder to the initiator.
7. **SharedSecret**: Computed during the **CASE** protocol execution and re-used when **CASE session resumption** is implemented.
8. **Local Message Counter**: **Secure Session Message Counter** for outbound messages.
 - At successful session establishment, the **Local Message Counter** SHALL be initialized per **Section 4.6.1.1, "Message Counter Initialization"**.
9. **Message Reception State**: Provides tracking for the **Secure Session Message Counter** of the remote peer.
10. **Local Fabric Index**: Records the local **Index** for the session's Fabric, which MAY be used to look up Fabric metadata related to the Fabric for which this session context applies.
 - This field SHALL contain the "no Fabric" value of 0 when the **SessionType** is **PASE** and successful invocation of the **AddNOC** command has not yet occurred during commissioning.
11. **Peer Node ID**: Records the authenticated node ID of the remote peer, when available.
 - This field SHALL contain the "Unspecified Node ID" value of 0 when the **SessionType** is **PASE**.