

```
cA [1] : OCTET STRING [length CRYPTO_HASH_LEN_BYTES],
}
```

On receipt of **Pake2**, the initiator SHALL:

1. Compute $TT := \text{Crypto_Transcript}(\text{PBKDFParamRequest}, \text{PBKDFParamResponse}, \text{Pake1.pA}, \text{Pake2.pB})$
2. Compute $(cA, cB, Ke) := \text{Crypto_P2}(TT, \text{Pake1.pA}, \text{Pake2.pB})$
3. Verify **Pake2.cB** against **cB**. If verification fails, the initiator SHALL send a **status report: Status-Report(GeneralCode: FAILURE, ProtocolId: SECURE_CHANNEL, ProtocolCode: INVALID_PARAMETER)** and perform no further processing.
4. Send a message with the appropriate **Protocol Id** and **Protocol Opcode** from Table 18, “Secure Channel Protocol Opcodes” whose payload is the TLV-encoded **pake-3-struct Pake3** with an anonymous tag for the outermost struct.

```
Pake3 =
{
  cA (1) = cA,
}
```

5. The initiator SHALL NOT send any encrypted application data until it receives **PakeFinished** from the responder.

On reception of **Pake3**, the responder SHALL:

1. Verify **Pake3.cA** against **cA**. If verification fails, the responder SHALL send a **status report: StatusReport(GeneralCode: FAILURE, ProtocolId: SECURE_CHANNEL, ProtocolCode: INVALID_PARAMETER)** and perform no further processing.
2. The responder SHALL set **SessionTimestamp** to a timestamp from a clock which would allow for the eventual determination of the last session use relative to other sessions.
3. The responder SHALL encode and send **PakeFinished**.

PakeFinished

To indicate the successful completion of the protocol, the responder SHALL send a **status report: StatusReport(GeneralCode: SUCCESS, ProtocolId: SECURE_CHANNEL, ProtocolCode: SESSION_ESTABLISHMENT_SUCCESS)**.

The initiator SHALL set **SessionTimestamp** to a timestamp from a clock which would allow for the eventual determination of the last session use relative to other sessions.

Session Encryption Keys

After verification of **Pake3**, each party can compute their sending and receiving session keys as described below:

```
byte SEKeys_Info[] = /* "SessionKeys" */
```