

```
{0x53, 0x65, 0x73, 0x73, 0x69, 0x6f, 0x6e, 0x4b,
  0x65, 0x79, 0x73}
```

```
I2RKey || R2IKey || AttestationChallenge =
  Crypto_KDF
  (
    inputKey = Ke,
    salt = [],
    info = SEKeys_Info,
    len = 3 * CRYPTO_SYMMETRIC_KEY_LENGTH_BITS
  )
```

1. Each key is exactly **CRYPTO_SYMMETRIC_KEY_LENGTH_BITS** bits.
2. The initiator SHALL use **I2RKey** to encrypt and integrity protect messages and the `R2IKey' to decrypt and verify messages.
3. The responder SHALL use **R2IKey** to encrypt and integrity protect messages and the `I2RKey' to decrypt and verify messages.
4. The **AttestationChallenge** SHALL only be used as a challenge during device attestation. See [Section 6.2.3, “Device Attestation Procedure”](#) for more details.

Upon initial installation of the new PASE Session Keys:

1. The Node SHALL initialize its **Local Message Counter** in the **Session Context** per [Section 4.6.1.1, “Message Counter Initialization”](#).
2. The Node SHALL initialize the **Message Reception State** in the **Session Context`** and set the synchronized **max_message_counter** of the peer to 0.

where **||** indicates message concatenation and **[]** a zero-length array.

4.14.2. Certificate Authenticated Session Establishment (CASE)

This section describes a certificate-authenticated session establishment (CASE) protocol using **Node Operational credentials**. This session establishment mechanism provides an authenticated key exchange between exactly two peers while maintaining privacy of each peer. A resumption mechanism allows bootstrapping a new session from a previous one, dramatically reducing the computation required as well as reducing the number of messages exchanged.

4.14.2.1. Protocol Overview

This session establishment protocol provides a means to:

1. Mutually authenticate both peer Nodes
2. Generate cryptographic keys to secure subsequent communication within a session
3. Exchange operational parameters for the session, such as **Session Identifier** and **MRP** param-