

ma1 message without any resumption fields to construct a Sigma2 message and continue the standard session establishment protocol without resumption.

To make the resumption succeed, both the Initiator and the Responder SHALL have remembered the SharedSecret they have computed during the previous execution of the CASE session establishment. It SHALL be that SharedSecret that is used to compute the resumption ID.

Session Resumption State

To perform session resumption, the following state from the previous session context must be known to the initiator and responder:

- 1. SharedSecret
- 2. Local Fabric Index
- 3. Peer Node ID
- 4. Peer CASE Authenticated Tags
- 5. ResumptionID

4.14.2.3. Protocol Details

Message format

All CASE messages SHALL be structured as specified in Section 4.4, “Message Frame Format”.

All CASE messages are sent using an Unsecured Session:

- The Session ID field SHALL be set to 0.
- The Session Type bits of the Security Flags SHALL be set to 0.
- In the CASE messages from the initiator, S Flag SHALL be set to 1 and DSIZ SHALL be set to 0.
- In the CASE messages from the responder, S Flag SHALL be set to 0 and DSIZ SHALL be set to 1.

For each CASE message, the application payload is the TLV encoding of the message structure as defined below:

Table 25. CASE Messages

Message Name	Payload TLV Encoding
Sigma1	sigma-1-struct
Sigma2	sigma-2-struct,
Sigma3	sigma-3-struct,
Sigma2_Resume	sigma-2-resume-struct,
SigmaFinished	N/A (encoded via StatusReport)

The other fields of the Message format are not specific to the CASE messages.