

```

resumption),
    initiatorResumeMIC      (7) = InitiatorResumeMIC (optional, only present if
performing resumption)
}

```

Validate Sigma1

On receipt of **Msg1**, the responder SHALL perform the following:

1. If **Msg1** contains either a **resumptionID** or an **initiatorResumeMIC** field **but not both**, the responder SHALL send a **status report**: **StatusReport**(GeneralCode: FAILURE, ProtocolId: SECURE_CHANNEL, ProtocolCode: INVALID_PARAMETER) and perform no further processing.
2. Set the **Peer Session Identifier** in the **Session Context** to the value **Msg1.initiatorSessionId**.
3. If **Msg1** contains both the **resumptionID** and **initiatorResumeMIC** fields, the responder SHALL search for an existing session that has a **Resumption ID** equal to the incoming **resumptionID**. If a single such session exists, the responder SHALL follow the steps in [Section 4.14.2.3.10](#), “**Validate Sigma1 with Resumption**” rather than continue the steps outlined in [Section 4.14.2.3.5](#), “**Validate Sigma1 Destination ID**”.
4. If **Msg1** does not contain a **resumptionID** and **initiatorResumeMIC** field, the responder SHALL continue the steps in [Section 4.14.2.3.5](#), “**Validate Sigma1 Destination ID**”.

Validate Sigma1 Destination ID

1. The responder SHALL validate the incoming **destinationId**:
 - a. The responder SHALL traverse all its installed **Node Operational Certificates (NOC)**, gathering the associated trusted roots' public keys from the associated chains and SHALL generate a **candidateDestinationId** based on the procedure in [Section 4.14.2.4.1](#), “**Destination Identifier**” for that tuple of <Root Public Key, Fabric ID, Node ID>.
 - b. The responder SHALL verify that the incoming **destinationId** matches one of the **candidateDestinationId** generated above. Upon such a match, the associated trusted root, Fabric ID, Node ID and IPK SHALL be recorded for subsequent use.
 - c. Note that at the initiator, only the current **Epoch Key** for the IPK will have been used. At the receiver, several IPK Epoch Keys may be installed, requiring several **candidateDestinationId** to be computed, one per available IPK Operational Key, per NOC.
2. If there is no **candidateDestinationId** matching the incoming **destinationId**, the responder SHALL send a **status report**: **StatusReport**(GeneralCode: FAILURE, ProtocolId: SECURE_CHANNEL, ProtocolCode: NO_SHARED_TRUST_ROOTS) and perform no further processing.
3. Otherwise, if a match was found for the **destinationId**, the matched **NOC**, **ICAC** (if present), and associated trusted root SHALL be used for selection of the **responderNOC** and **responderICAC** in the steps for **Sigma2**.

Generate and Send Sigma2

If **validation** is successful, the responder encodes and sends a **Sigma2** message.