

```

    K = S2K,
    C = Msg2.encrypted2,
    A = TBEData2_A,
    N = TBEData2_Nonce
)

```

4. If the value of **Success** is **FALSE**, the initiator SHALL send a **status report**: **StatusReport(GeneralCode: FAILURE, ProtocolId: SECURE_CHANNEL, ProtocolCode: INVALID_PARAMETER)** and perform no further processing.
5. The initiator SHALL verify that the **NOC** in **TBEData2.responderNOC** and **ICAC** in **TBEData2.responderICAC** (if present) fulfills the following constraints:
 - a. The Fabric ID and Node ID SHALL match the intended identity of the receiver Node, as included in the computation of the **Destination Identifier** when generating Sigma1.
 - b. If an **ICAC** is present, and it contains a Fabric ID in its subject, then it SHALL match the FabricID in the NOC leaf certificate.
 - c. The certificate chain SHALL chain back to the Trusted Root CA Certificate **TrustedRCAC** whose public key was used in the computation of the **Destination Identifier** when generating Sigma1.
 - d. All the elements in the certificate chain SHALL respect the **Matter Certificate DN Encoding Rules**, including range checks for identifiers such as Fabric ID and Node ID.
6. If any of the validations from the previous step fail, the initiator SHALL send a **status report**: **StatusReport(GeneralCode: FAILURE, ProtocolId: SECURE_CHANNEL, ProtocolCode: INVALID_PARAMETER)** and perform no further processing.
7. The initiator SHALL verify **TBEData2.responderNOC** using:
 - a. **Success = Crypto_VerifyChain(certificates = [TBEData2.responderNOC, TBEData2.responderICAC, TrustedRCAC])**, when **TBEData2.responderICAC** is present, or
 - b. **Success = Crypto_VerifyChain(certificates = [TBEData2.responderNOC, TrustedRCAC])**, when **TBEData2.responderICAC** is not present.
8. If the value of **Success** is **FALSE**, the initiator SHALL send a **status report**: **StatusReport(GeneralCode: FAILURE, ProtocolId: SECURE_CHANNEL, ProtocolCode: INVALID_PARAMETER)** and perform no further processing.
9. The initiator SHALL encode the following items as a **sigma-2-tbsdata** with an **anonymous tag**:
 - a. **responderNOC** as copied from **TBEData2**
 - b. **responderICAC** (if present) as copied from **TBEData2**
 - c. **Msg2.responderEphPubKey**
 - d. **InitiatorEphKeyPair.publicKey**
10. The initiator SHALL **verify** **TBEData2.signature** (see **RFC 5280**):

```

Success = Crypto_Verify(
    publicKey = Public key obtained from responderNOC,

```