

)

3. If **Success** is FALSE, the initiator SHALL send a **status report**: **StatusReport**(GeneralCode: FAILURE, ProtocolId: SECURE_CHANNEL, ProtocolCode: INVALID_PARAMETER_) and perform no further processing.
4. The initiator SHALL set the **Resumption ID** in the **Session Context** to the value **Resume2Msg.resumptionID**.
5. The initiator SHALL generate the session keys as described in [Section 4.14.2.6.7](#), “**Resumption Session Encryption Keys**”.
6. The initiator SHALL reset its **Local Message Counter** in the **Session Context** per [Section 4.6.1.1](#), “**Message Counter Initialization**”.
7. The initiator SHALL reset the **Message Reception State** of the **Session Context** and set the synchronized **max_message_counter** of the peer to 0.
8. The initiator SHALL set **SessionTimestamp** to a timestamp from a clock which would allow for the eventual determination of the last session use relative to other sessions.
9. The initiator SHALL set the **Peer Session Identifier** in the **Session Context** to the value **ResumeMsg2.responderSessionId**.
10. The initiator SHALL send [Section 4.14.2.3.13](#), “**SigmaFinished**”.

SigmaFinished

To indicate the successful completion of the protocol, the Node receiving Sigma3 (if a new session is being established) or Sigma2_Resume (if a session is being resumed) SHALL send a **status report**: **StatusReport**(GeneralCode: SUCCESS, ProtocolId: SECURE_CHANNEL, ProtocolCode: SESSION_ESTABLISHMENT_SUCCESS).

On successful receipt of **SigmaFinished**:

1. The receiving node SHALL initialize the **Local Message Counter** according to [Section 4.6.1.1](#), “**Message Counter Initialization**” for the newly established secure session whose success is acknowledged by this message.
2. The receiving node SHALL set **SessionTimestamp** to a timestamp from a clock which would allow for the eventual determination of the last session usage relative to other sessions.

If this message is received out-of-order or unexpectedly, then it SHALL be ignored.

4.14.2.4. Field Descriptions

Destination Identifier

destination-identifier => OCTET STRING [length CRYPTO_HASH_LEN_BYTES]

The Destination Identifier field enables the initiator of the **Sigma1** message to unambiguously express the following, in a privacy-preserving manner: