

```
TranscriptHash = Crypto_Hash(message = Msg1)
```

2. The Sigma2 key SHALL be [generated](#):

```
byte S2K_Info[] = /* "Sigma2" */
    {0x53, 0x69, 0x67, 0x6d, 0x61, 0x32}

S2K = Crypto_KDF(
    inputKey = SharedSecret,
    salt = IPK || Responder Random || Responder Ephemeral Public Key ||
    TranscriptHash,
    info = S2K_Info,
    len = CRYPTO_SYMMETRIC_KEY_LENGTH_BITS
)
```

where `||` indicates message concatenation and **IPK** is generated according to [Section 4.14.2.6.1](#), “Identity Protection Key (IPK)”.

Sigma3 Key (S3K)

1. A transcript hash SHALL be [generated](#):

```
TranscriptHash = Crypto_Hash(message = Msg1 || Msg2)
```

2. The Sigma3 key SHALL be [generated](#):

```
byte S3K_Info[] = /* "Sigma3" */
    {0x53, 0x69, 0x67, 0x6d, 0x61, 0x33}

S3K = Crypto_KDF(
    inputKey = SharedSecret,
    salt = IPK || TranscriptHash,
    info = S3K_Info,
    len = CRYPTO_SYMMETRIC_KEY_LENGTH_BITS
)
```

where `||` indicates message concatenation and **IPK** is generated according to [Section 4.14.2.6.1](#), “Identity Protection Key (IPK)”.

Sigma1 Resumption Key

The Sigma1 resumption key SHALL be [generated](#):