

```

    0x65, 0x79, 0x73}

I2RKey || R2IKey || AttestationChallenge = Crypto_KDF(
    inputKey = SharedSecret,
    salt = IPK || TranscriptHash,
    info = SEKeys_Info,
    len = 3 * CRYPTO_SYMMETRIC_KEY_LENGTH_BITS
)

```

- Each key is exactly **CRYPTO_SYMMETRIC_KEY_LENGTH_BITS** bits.
- The initiator SHALL use **I2RKey** to encrypt and integrity protect messages and the `R2IKey' to decrypt and verify messages.
- The responder SHALL use **R2IKey** to encrypt and integrity protect messages and the `I2RKey' to decrypt and verify messages.
- The **AttestationChallenge** SHALL only be used as a challenge during device attestation. See [Section 6.2.3, “Device Attestation Procedure”](#) for more details.

where `||` indicates message concatenation.

Resumption Session Encryption Keys

- The resumption session encryption keys SHALL be [generated](#):

```

byte RSEKeys_Info[] = /* "SessionResumptionKeys" */
    {0x53, 0x65, 0x73, 0x73, 0x69, 0x6f, 0x6e, 0x52,
     0x65, 0x73, 0x75, 0x6d, 0x70, 0x74, 0x69, 0x6f,
     0x6e, 0x4b, 0x65, 0x79, 0x73}

I2RKey || R2IKey || AttestationChallenge = Crypto_KDF(
    inputKey = SharedSecret,
    salt = Sigmal.initiatorRandom || ResumptionID,
    info = RSEKeys_Info,
    len = 3 * CRYPTO_SYMMETRIC_KEY_LENGTH_BITS
)

```

- Each key is exactly **CRYPTO_SYMMETRIC_KEY_LENGTH_BITS** bits.
- The initiator SHALL use **I2RKey** to encrypt and integrity protect messages and the `R2IKey' to decrypt and verify messages.
- The responder SHALL use **R2IKey** to encrypt and integrity protect messages and the `I2RKey' to decrypt and verify messages.
- The **AttestationChallenge** SHALL only be used as a challenge during device attestation. See [Section 6.2.3, “Device Attestation Procedure”](#) for more details.