

where `||` indicates message concatenation and `ResumptionID` is the new identifier for the this session.

4.14.2.7. Session Context Storage

After the session is established successfully at both peers, some fields SHALL be recorded in the secure session context for later use (see [Section 4.13.3, “Application Data Phase”](#)), in addition to the [Session Encryption Keys](#):

- The peer NOC's `matter-node-id` ([1.3.6.1.4.1.37244.1.1](#)) from the subject field
- The [Section 2.5.1, “Fabric References and Fabric Identifier”](#) for the Fabric within which this secure session is being established
- All peer NOC's `case-authenticated-tag` ([1.3.6.1.4.1.37244.1.6](#)) from the subject field, if present

These fields MAY be recorded at any opportune point during the protocol, but SHALL only be committed to the secure session context once the session is established successfully at both peers.

4.14.2.8. Minimal Number of CASE Sessions

A node SHALL support at least 3 CASE session contexts per fabric. Device type specifications MAY require a larger minimum. Unless the device type specification says otherwise, a minimum number it defines is a per-fabric minimum.

The minimal supported capabilities, subject to the minimal constraints above, are reported in the [CapabilityMinima](#) of the [Basic Information cluster](#).

- Example: If a device type requires at least 4 CASE session contexts, and a node supports 7 fabrics, the node would support at least 28 CASE session contexts, and ensure that each fabric could use at least 4 of them.

4.15. Secure Communications over TCP

Matter messages over [MRP](#) need to be sized so that each UDP datagram fits within an IPv6 MTU limit of 1280 bytes, to avoid IPv6 fragmentation and reassembly. Thus, larger messages cannot be transferred over MRP unless the application explicitly performs fragmentation and reassembly. Therefore, nodes that need to send [large command messages](#) must use an alternative transport protocol, such as TCP. TCP support is communicated by nodes through the [TXT record key T](#) in their DNS-SD operational service records.

Since TCP already provides message transmission reliability, a node that is using TCP as the underlying transport protocol SHALL NOT use MRP reliability semantics on its message exchanges.

4.15.1. Secure Session Establishment

When a pair of nodes that both support TCP intend to establish a secure session between themselves, they MAY choose TCP as the underlying transport protocol. With a given peer, a node SHOULD, typically, either have a secure session over MRP or one over TCP, but MAY also have both. For example, a node might be using MRP for all its interactions with a controller, but might set up a session over TCP with the same for specific data-heavy operations such as OTA.