

bit 0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Final Protocol Version				Reserved				Selected ATT_MTU (low byte)...							
...Selected ATT_MTU (high byte)								Selected Window Size							

H (Handshake) bit

Set to '1' for session handshake messages.

M (Management) bit

Set to '1' for session handshake messages.

Final Protocol Version

Value of the BTP protocol version selected by the server.

Reserved

Must be set to '0'.

Selected ATT_MTU

Value of the maximum ATT_MTU for the connection selected by the server as a 16-bit unsigned integer.

Selected Window Size

Value of the maximum receive window size supported by the server, specified in units of BTP packets where each packet may be up to the selected segment size in length.

4.19.4. BTP GATT Service

4.19.4.1. BTP Channelization

Bluetooth Transport Protocol provides a packetized stream interface over GATT but says nothing about the actual contents of the data packets it transports. The BTP Service UUID is used to specify the actual contents of the packets (see [Table 33, “BTP Service UUID”](#)).

Table 33. BTP Service UUID

BTP Datagram Contents	BTP Service UUID
Matter Message frames	MATTER_BLE_SERVICE_UUID

NOTE

See [Section 4.19.6, “Bluetooth Requirements”](#) for terms of use.

While a single BTP connection may exist between a BTP Client and BTP Server, multiple BTP sessions may be established between various peers.