

B (Beginning Segment) bit

Set to '1' on the first segment of a PAFTP SDU and set to '0' for all remaining segments of the same PAFTP SDU. It indicates the presence of the Message Length field.

4.20.2.2. Ack Number

Optional field specified in [Section 4.20.3.8, “Packet Acknowledgements”](#).

4.20.2.3. Sequence Number

Mandatory field for regular data messages specified in [Section 4.20.3.6, “Sequence Numbers”](#).

4.20.2.4. Message Length

Optional field present in Beginning Segment only. Value indicates the length in bytes of the full message buffer to be transmitted. None of the PAFTP Packet PDU fields is included in the Message Length.

4.20.2.5. Segment Payload

Optional field containing a segment of the Service Data Unit (SDU) message in transmission to the receiver.

4.20.3. PAFTP Control Frames

PAFTP defines different control frame formats depending on the Management Opcode that is in the PAFTP Packet PDU header. Valid Management Opcodes for PAFTP Control Frames are defined in [Table 39, “PAFTP Control codes”](#).

Table 39. PAFTP Control codes

Management Opcode	Name	Description
0x6C	Handshake	Request and response for PAFTP session establishment

4.20.3.1. PAFTP Handshake Request

Table 40. PAFTP Handshake Request format

bit 0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Control Flags = 0x65								Management Opcode = 0x6C							
Ver[0]				Ver[1]				Ver[2]				Ver[3]			
Ver[4]				Ver[5]				Ver[6]				Ver[7]			
Supported Maximum Service Specific Info length															
Commissioner Window Size															