

Bit	Size (bits)	Description
3	1	Wi-Fi Public Action Frame: 0: Device does not support Wi-Fi Public Action Frame for discovery or is currently commissioned into one or more fabrics. 1: Device supports Wi-Fi Public Action Frame for discovery when not commissioned.
4	1	NFC Transport Layer: 0: Device does not support NFC Transport Layer (NTL) for commissioning or is currently commissioned into one or more fabrics. 1: Device supports NFC Transport Layer (NTL) for commissioning when not commissioned.
7..5	3	Reserved (SHALL be 0)

TLV Data

The TLV data is an optional, variable-length payload. The payload is composed of one or more TLV-encoded elements as defined in detail below in the [TLV Content](#) section.

Encoding

The Packed Binary Data Structure is Base-38 encoded (with a specific alphabet) to produce an alphanumeric string suitable for use as a QR code payload.

Alphabet

The Base-38 alphabet to be employed is composed of a subset of the 45 available characters ([A-Z0-9\\$%*+./ :-](#)) in the QR code for alphanumeric encoding as defined by [ISO/IEC 18004:2015](#), with characters [\\$, %, *, +, /, <space>](#), and [:](#) removed.

Table 59. Alphabet for Onboard Payload Encoding

Code	Character	Code	Character	Code	Character	Code	Character	Code	Character
00	0	09	9	18	I	27	R	36	-
01	1	10	A	19	J	28	S	37	.
02	2	11	B	20	K	29	T		
03	3	12	C	21	L	30	U		
04	4	13	D	22	M	31	V		
05	5	14	E	23	N	32	W		
06	6	15	F	24	O	33	X		
07	7	16	G	25	P	34	Y		
08	8	17	H	26	Q	35	Z		