

A Commissioner which performs [Device Discovery](#) without knowledge of the Onboarding Payload may discover devices on the network that the user did not intend to commission with the given Commissioner. This additional information collected by the Commissioner can be associated with the user in ways that the user did not intend.

5.2.2.4. Commissioner Discovery, from an On-Network Device

"Launch Device User Interface, Discover Commissioners"

In the Commissioner Discovery use case for a Device already on the IP network, the User first initiates an interaction with the Device via a display or other user interface, and indicates the intention to have this device commissioned by a Commissioner on the network. The Device might already have been commissioned into one or more Fabrics or it might not yet have been commissioned. Upon this user interaction, the Device discovers candidate Commissioners and allows the user to select one. The Device then requests from that Commissioner to be commissioned.

5.2.2.4.1. Rationale

In this use case, a Device (Commissionee) with a user interface, such as a TV or Thermostat, initiates the commissioning process. For example, this might be done from within a settings menu for Smart Home control. The Device discovers Commissioners on the IP-bearing network, presents the resulting list to the User for selection. Once selected, the Device indicates to the selected Commissioner that it has been selected by the User, the Device enters Commissioning Mode and provides the onboarding payload to the User.

Another example for this use case is a Device or Node (Commissionee) with a user interface, such as a Content Provider Device or Application, that initiates the commissioning process. This might be done from a program guide or while watching a video when the user indicates a desire to play the selected content on a nearby device. The Device discovers Commissioners on the IP-bearing network, presents the resulting list to the User for selection. Once selected, the Commissionee indicates to the selected Commissioner that it has been selected by the User (see [Section 5.3, "User Directed Commissioning"](#)), the Commissionee enters Commissioning Mode and provides the onboarding payload to the User.

5.2.2.4.2. High Level Flow

1. User initiates an interaction with the Device.
2. User indicates a desire to connect this Device with a Commissioner on the network.
3. Device uses [Commissioner Discovery](#) over DNS-SD on the IP bearing network.
4. Device collects candidates from DNS-SD service records found.
5. Device displays list of Commissioners discovered, including as much information as possible from the DNS-SD TXT record. When a Vendor ID and Product ID is provided (see [Section 4.3.1.6, "TXT key for Vendor ID and Product ID \(VP\)"](#)), the Device may obtain human readable descriptions of the Vendor and Product in order to assist the user with selection by using fields such as [ProductName](#) and [ProductLabel](#) from the [Distributed Compliance Ledger](#) or any other data set available to it. The Device may have additional data sets available for assisting the user. When the Device Type (see [Section 4.3.1.8, "TXT key for device type \(DT\)"](#)) and/or the Device Name (see [Section 4.3.1.9, "TXT key for device name \(DN\)"](#)) values are provided in the DNS-SD TXT record,