

then the Device may provide this information to the user in order to assist with Commissioner selection.

6. User selects an entry from the list.
7. Device enters Commissioning Mode.
8. Device displays onboarding payload to the user.
9. Device initiates a [Section 5.3, “User Directed Commissioning”](#) session with the selected Commissioner, which includes in the DNS-SD service name of the Device.
10. Commissioner prompts user to confirm intention to commission this device and asks for onboarding payload.
11. User enters onboarding payload into Commissioner UX.
12. Commissioner begins the commissioning process (see [Section 5.5, “Commissioning Flows”](#)).

For additional variations relating to the display and input of the onboarding payload, see [Section 5.3, “User Directed Commissioning”](#).

5.2.2.4.3. Misuse Considerations

In addition to the Misuse Considerations described in [Section 5.2.2.3, “User-Initiated Beacon Detection, Already Commissioned Device”](#), a Commissionee which performs [Commissioner Discovery](#) may discover Commissioners on the network that the user did not intend to be discovered by the given Commissionee. This additional information collected by the Commissionee can be associated with the user in ways that the user did not intend. See [Commissioner Discovery Privacy Considerations](#) for Commissioner requirements relating to this risk.

Since there are no trust mechanisms employed for Commissioners advertising themselves, Commissionees may provide Commissioner selection choices to the User that are from malicious entities masquerading as commissioners.

When a Commissioner includes device-specific information such as Vendor ID, Product ID and Device Type, or user-generated data such as Device Name, in the DNS-SD TXT record, then a malicious actor on the network can detect this information and potentially associate it with the user in ways that the user did not intend.

5.3. User Directed Commissioning

5.3.1. Overview

In User Directed Commissioning (UDC), the Commissionee sends a message to the Commissioner in order to initiate the commissioning process (see [Section 5.5, “Commissioning Flows”](#)). In addition, the Commissionee can specify its UX preferences for the commissioning session using optional parameters in the message. Similarly, the Commissioner can send a message to the Commissionee to indicate its pre-commissioning state in order to help the Commissionee simplify the experience for the user.

The availability of the UDC protocol is advertised through Commissioner Discovery service records of DNS-SD service type `_matterd._udp` (see [Section 4.3.3, “Commissioner Discovery”](#)).