

In this scenario, the Commissioner generates a Passcode and displays it for the user. The user enters the Passcode into the Commissionee UX. The Commissionee UX generates a PASE verifier based upon this Passcode and enters commissioning mode using this PASE verifier. The Commissionee then notifies the Commissioner that it is in commissioning mode (using the new PASE verifier) by sending a IdentificationDeclaration with the **CommissionerPasscodeReady** field set to true.

If, in addition to dynamic passcodes, the Commissioner provides a fixed passcode option, it SHALL be user-updatable and the Commissioner SHALL provide an option to the user to reset the fixed passcode frequently, and SHALL provide an option to disable the fixed passcode feature.

A Commissioner indicates that it supports this feature via the **CP** txt record in [Commissionable Node Discovery](#).

A Commissionee can utilize this feature via the **CommissionerPasscode** and **CommissionerPasscodeReady** fields.

The Commissionee can also inform the Commissioner that the user has declined or exited the commissioning process by using the **CancelPasscode** field in the IdentificationDeclaration message.

See [Section 5.3.7.5, “UDC with Commissioner-generated Passcode”](#).

5.3.5.2. Parameters

This following table lists the parameters used in IdentificationDeclaration with a brief description for each parameter and the feature that uses it.

Table 67. List of IdentificationDeclaration parameters

Parameter Name	Feature	Description
instanceName	Always Required	The DNS-SD instance name defined in Commissionable Node Discovery .
VendorId	Bypass Commissionable Node Discovery	The Vendor ID provided as input to the mdns TXT records (see Section 4.3.1.6, “TXT key for Vendor ID and Product ID (VP)”).
ProductId	Bypass Commissionable Node Discovery	The Product ID provided as input to the mdns TXT records (see Section 4.3.1.6, “TXT key for Vendor ID and Product ID (VP)”).
DeviceName	Bypass Commissionable Node Discovery	The device name as described in the mdns TXT records (see Section 4.3.1.9, “TXT key for device name (DN)”).
DeviceType	Bypass Commissionable Node Discovery	The device type as described in the mdns TXT records (see Section 4.3.1.8, “TXT key for device type (DT)”).
PairingInstruction	Bypass Commissionable Node Discovery	The pairing instruction as described in the mdns TXT records (see Section 4.3.1.12, “TXT key for pairing instructions (PI)”).