

Argument	Description	Value for discovery
configuration_parameters	Miscellaneous configuration parameters	Publish Type = unso- licited and solicited transmissions Discovery range = 0 Solicited transmission type = unicast Announcement period = (<i>see text below</i>) Time to live = (<i>see text below</i>) Event conditions = always Matching filter flag = 1 NAN Ranging Flag = 0 Data Path Flag = 0 Awake DW Interval = Not Applicable Further Service Discovery flag = 1 Further Service Discovery function = 0 NAN Discovery flag = 1 Default Publish Channel = 6 Publish Channel List = [all 20 MHz chan- nels in 2.4 GHz band and 5 GHz band (if supported), per regulation in the geo- graphical region] Nmin = 5 Nmax = 10 Mmin = 5 Mmax = 10

Table 75. Wi-Fi Public Action Frame Device OpCode

Device OpCode Value	Description
0x00	Commissionable
0x01	NetworkRecovery
0x02 - 0xFF	Reserved

Table 76. Wi-Fi Public Action Frame Device Information

Bits	Description
b15:b12	Advertisement version, set to 0x0
b11:b0	12-bit discriminator (see Section 5.4.2.4.1, “Discriminator”)

Some devices MAY choose not to advertise the Vendor ID and/or Product ID due to privacy or other considerations. These devices SHALL set the Vendor ID and Product ID to value 0 in the **service_specific_info**. Extended Data is optionally present in **service_specific_info**. The **Time to live** value is set according to [Section 5.4.2.3, “Announcement Duration”](#). The recommended value of **Announcement period** is 100 TUs. 1 TU is equal to 1024 microseconds.

Single-channel Publish State and Multiple-channels Publish State defined in [WFA-USD](#) govern the advertisement behavior.