

1. Single-channel Publish State: The Commissionable device operates in the Default Publish Channel during this state. The dwell period (the time spent on a channel) is randomly determined as $N \times 100$ TU, where N is an integer randomly selected within the range [N_{min} , N_{max}].
2. Multiple-channels Publish State: In this state, the publisher can operate in one or more channels from the Publish Channel List. The dwell period is randomly determined as $M \times 100$ TU, where M is an integer randomly selected within the range [M_{min} , M_{max}]. The implementation of [WFA-USD](#) has flexibility to divide the dwell period across the channels in the Publish Channel List. The Commissionable device MAY publish on a subset of channels within each multiple-channels Publish State, and the minimum time spent on any one channel is 100 ms in [WFA-USD](#).

If a device opts to use [Extended Announcement](#), it SHALL switch to using N_{min} , N_{max} , M_{min} , and M_{max} greater than or equal to 10, 15, 10, 15, respectively, and SHOULD use an [Announcement period](#) of 1000 TUs.

NOTE These recommended values may be updated in a future version of the specification.

5.4.2.7. Using Existing IP-bearing Network

This section details how a device that is already connected to an IP-bearing network advertises its commissionable state. The discovery protocols leverage IETF Standard DNS-based Service Discovery [[RFC 6763](#)]. A device SHALL use multicast DNS [[RFC 6762](#)] on Wi-Fi and Ethernet networks to make itself discoverable. On Thread networks, a device SHALL use the Service Registration Protocol [[SRP](#)] and an Advertising Proxy [[AdProx](#)] running on a Thread Border Router to make itself discoverable. Additional details on application of the above protocols in Matter is found in [Section 4.3, “Discovery”](#). The encoding of the information required for discovery during the commissioning process is covered in [Section 4.3.1, “Commissionable Node Discovery”](#).

5.4.2.8. Manufacturer-specific data

If needed, manufacturer-specific data MAY be advertised by a commissionable device using one of the following mechanisms, based on the supported commissioning technology. Commissioners receiving this data SHOULD treat it as opaque unless they have the need to and possess the ability to correctly interpret the information conveyed.

5.4.2.8.1. Using BLE

Any manufacturer-specific data may be included as a Manufacturer Specific Data AD type in the Advertising Data or in the Scan Response data.

Note that to receive Scan Response data information the Commissioner has to perform BLE active scanning that, in addition to creating additional traffic in the shared 2.4 GHz unlicensed band, can delay device discovery and connection, increasing the overall time required to commission a device.

5.4.2.8.2. Using Wi-Fi Public Action Frame

Any manufacturer-specific data SHOULD be conveyed using the Vendor-specific attributes in [WFA-USD](#).