

- The presence of this field is to assist automatically resuming commissioning without additional data entry (QR code or Manual Pairing Code) by the user at the Commissioner that initially triggered the custom flow. The manufacturer custom flow SHOULD provide an alternate means of conveying the onboarding payload, such as a manual pairing code.
- Note that if the information in the initial onboarding payload that caused triggering of a Custom Commissioning Flow was directly usable, it may be used by the Commissioner, either upon being triggered through the `ExpandedCallbackUrl` having been opened, or autonomously as a fallback.
- Commissioners providing a `CallbackUrl` to the manufacturer custom flow through the `ExpandedCommissioningCustomFlowUrl` SHOULD support using the `ExpandedCallbackUrl` to trigger resumption of Commissioning flow if the `ExpandedCallbackUrl` is followed, otherwise the Commissioner SHOULD NOT substitute the `MTcu` query field when expanding the `CommissioningCustomFlowUrl` into the `ExpandedCommissioningCustomFlowUrl`.
- If the manufacturer custom flow failed to make the device commissionable, it SHALL NOT replace the placeholder value "_" of an included `MTrop=_` key/value pair, to avoid a Commissioner attempting to discover or commission a device not made ready by the custom flow.

A manufacturer custom flow having received an `ExpandedCommissioningCustomFlowUrl` SHOULD attempt to open the `ExpandedCallbackUrl`, on completion of the steps, if an `ExpandedCallbackUrl` was computed from the `CallbackUrl` and opening such a URL is supported.

5.7.3.3. Examples of CommissioningCustomFlow URLs

Below are some examples of valid `ExpandedCommissioningCustomFlowUrl` for several valid values of `CommissioningCustomFlowUrl`, as well as some examples of invalid values of `CommissioningCustomFlowUrl`:

- Valid URL with no query string:
 - Before expansion: <https://company.domain.example/matter/custom/flows/vFFF1p1234>
 - After expansion: <https://company.domain.example/matter/custom/flows/vFFF1p1234> (no change)
- Invalid URL with no query string: `http` scheme is not allowed:
 - <http://company.domain.example/matter/custom/flows/vFFF1p1234>
- Valid URL with basic manufacturer-specific scheme for query:
 - Before expansion: <https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234>
 - After expansion: <https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234> (no change)
- Valid URL with `MTop=_` placeholder using QR format onboarding payload embedding:
 - Before expansion: https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234&MTop=_
 - After expansion: <https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234&MTop=MT%3A-MOA57ZU02IT2L2BJ00>