

- Onboarding payload QR content **MT: -M0A57ZU02IT2L2BJ00** was embedded within **MTop** key
- Valid URL with **MTop=_** placeholder using Manual Pairing Code onboarding payload embedding:
 - Before expansion: https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234&MTop=_
 - After expansion: <https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234&MTop=610403146665521046600>
 - Onboarding Manual Pairing Code **610403146665521046600** was embedded within **MTop** key
- Valid URL with **MTop=_** placeholder using Manual Pairing Code onboarding payload embedding, using a different order of keys/value pairs than the previous example:
 - Before expansion: https://company.domain.example/matter/custom/flows?pid=1234&MTop=_&vid=FFF1
 - After expansion: <https://company.domain.example/matter/custom/flows?pid=1234&MTop=610403146665521046600&vid=FFF1>
 - Onboarding Manual Pairing Code **610403146665521046600** was embedded within **MTop** key
- Valid URL with onboarding payload elided (because commissioner could not provide it):
 - Before expansion: https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234&MTop=_
 - After expansion: https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234&MTop=_ (no change)
- Valid URL, return onboarding payload and **CallbackUrl** requested:
 - Before expansion:

```
https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234&MTop=_&MTcu=_
```

- After expansion:

```
https://company.domain.example/matter/custom/flows?vid=FFF1&pid=1234&MTop=MT%3A-M0A57ZU02IT2L2BJ00&MTcu=https%3A%2F%2Fcommissioner.domain.example%2Fcb%3Ftoken%3DmAsJ6_vqbr-vjDiG_w%253D%253D%26MTrop%3D_
```

- The **ExpandedCommissioningCustomFlow** URL contains:
 - An embedded onboarding payload QR content value of **MT: -M0A57ZU02IT2L2BJ00**
 - A **CallbackUrl** with a Commissioner-provided arbitrary **token=** key/value pair and the **MTrop=** key/value pair place-holder to indicate support for a return onboarding payload: https://commissioner.domain.example/cb?token=mAsJ6_vqbr-vjDiG_w%3D%3D&MTrop=_
 - After expansion of the **CallbackUrl** (**MTcu** key) into an **ExpandedCallbackUrl**, with an example return onboarding payload of **MT: -M0A5.GB00V68T62010**, the **ExpandedCallbackUrl** would be: