

- i. Both the **keyCertSign** and **cRLSign** bits SHALL be set in the **KeyUsage** bitstring
 - ii. The **digitalSignature** bit MAY be set in the **KeyUsage** bitstring
 - iii. Other bits SHALL NOT be set
 - c. Subject Key Identifier
11. The certificate MAY also carry the following additional Extensions:
- a. Extended Key Usage
 - b. Authority Key Identifier
 - c. Any other extension allowed in [RFC 5280](#) where inclusion does not violate size limitations. These extensions insofar not defined in this specification SHALL be ignored by commissioners conforming to this specification, but MAY be present to allow flexibility in CA operation.

The PAA certificate presented in the following example is for the issuer of the example PAI certificate from the previous section.

Valid example PAA with associated private key, in [X.509 PEM](#) format

```
-----BEGIN CERTIFICATE-----
MIIBvTCCAWsGAwIBAgIITqjoMYLUHBwwCgYIKoZIzj0EAwIwMDEYMBYGA1UEAwP
TWf0dGVyIFRlc3QgUEFBRQwEgYKKwYBBAGConwCAQwERkZGNTAgFw0yMTA2Mjgx
NDIzNDNaGA850Tk5MTIzMTIzNTk1OVowMDEYMBYGA1UEAwPTWf0dGVyIFRlc3Qg
UEFBRQwEgYKKwYBBAGConwCAQwERkZGNTBZMBMBGByqGSM49AgEGCCqGSM49AwEH
A0IABLbLY3KI fyko9brIGqnZ0uJDHK2p154kL2UXfvn02TKijs0Duq9qj8oYShpQ
NUKWDUU/MD8fGUIdR6Pjxqam3WjZjBkMBIGA1UdEwEB/wQIMAYBAf8CAQEwDgYD
VR0PAQH/BAQDAgEGMB0GA1UdDgQWBBRq/SJ3H1Ef7L8WQZdnENzcMaFxfjAfBgNV
HSMEGDAwBRq/SJ3H1Ef7L8WQZdnENzcMaFxfjAKBgqhkhjOPQDAGNHADBEAiBQ
qoAC9NkyqaAFOPZTaKOP/8jvu8m+t9pWmDXPmqdRDgIgI7rI/g8j51RFtLM5CBpH
mUkpxyqvChVI1A0DTVFLJd4=
-----END CERTIFICATE-----

-----BEGIN EC PRIVATE KEY-----
MHcCAQEEIGUSyuyuz8VD1gYjFhWXF i8BRoTFZaEpti/SjCerHMxQoAoGCCqGSM49
AwEHoUQDQgAETstjcoh/KSj1usgaqdk64kMcranXniQvZrD++c7ZMqK0zQ06r2qP
yhhKGLA1QpYNRT8wPx8ZQh11Ho+PGpqbdQ==
-----END EC PRIVATE KEY-----
```

Human-readable contents of example PAA X.509 certificate

Certificate:

Data:

Version: 3 (0x2)

Serial Number: 5668035430391749660 (0x4ea8e83182d41c1c)

Signature Algorithm: ecdsa-with-SHA256

Issuer: CN = Matter Test PAA, 1.3.6.1.4.1.37244.2.1 = FFF1