

The procedure is as follows:

1. The Commissioner SHALL generate a random 32 byte attestation nonce using `Crypto_DRBG()`.
2. The Commissioner SHALL send the `AttestationNonce` to the Commissionee and request Attestation Information using `AttestationRequest`.
3. The Commissionee SHALL return the signed `Attestation Information` to the Commissioner using `AttestationResponse`.

After execution of the procedure, the Attestation Information SHOULD be validated using the checks described in [Section 6.2.3.1, “Attestation Information Validation”](#).

6.2.3.1. Attestation Information Validation

A Commissioner validating the Attestation Information SHOULD record sufficient information to provide detailed results of the validation outcome to users. Therefore, prior to validating Attestation Information, a Commissioner SHOULD have previously obtained the Device Attestation Certificate chain for the Commissionee, so that the DAC and PAI necessary for the procedure are available.

In order to consider a Commissionee successfully attested, a Commissioner SHALL have successfully validated at least the following:

- The PAA SHALL be validated for presence in the Commissioner’s trusted root store, which SHOULD include at least the set of globally trusted PAA certificates present in the [Distributed Compliance Ledger](#) at the issuing timestamp (`notBefore`) of the DAC.
- The DAC certificate chain SHALL be validated using the `Crypto_VerifyChainDER()` function, taking into account the mandatory presence of the PAI and of the PAA. It is especially important to ensure the entire chain has a length of exactly 3 elements (PAA certificate, PAI certificate, Device Attestation Certificate) and that the necessary format policies previously exposed are validated, to avoid unauthorized path chaining (e.g., through multiple PAI certificates).
 - Chain validation SHALL be performed with respect to the `notBefore` timestamp of the DAC to ensure that the DAC was valid when it was issued. This way of validating is abided by the `Crypto_VerifyChainDER()` function.
 - Chain validation SHALL include revocation checks of the DAC and PAI, based on the Commissioner’s best understanding of revoked entities. See [Section 6.2.4, “Device attestation revocation”](#) for an interoperable method of obtaining revocation information in the Device Attestation PKI.
- The `VendorID` value found in the subject DN of the DAC SHALL match the `VendorID` value in the subject DN of the PAI certificate.
- If the PAA certificate contains a `VendorID` value in its subject DN, its value SHALL match the `VendorID` value in the subject DN of the PAI certificate.
- The Device Attestation Signature (`attestation_signature`) field from `Attestation Response` SHALL be validated:

```
Success = Crypto_Verify(  
    publicKey = Public key from DAC,
```